

backings specifications

Duralon II Attached Cushion with Moisture Barrier

Product Specification Duralon II MB is a registered trade name for Durkan Hospitality a Division of Mohawk Industries. Duralon II MB is an ergonomically correct attached composite rubber cushion composed of latex precoat, moisture-barrier coating, gel-foam and inlaid woven Actionbac. Duralon II MB is limited in use to Durkan prints and beck-dyed solids.

Duralon II MB is an applicable backing system for hospitality, institutional and healthcare environments. Moisture-barrier, acoustical and insulative values add to the performance characteristics of Duralon II MB.

Binding Material	30-32 ozs. Latex Precoat 15 ozs. Moisture-resistant Precoat
Foam Weight	33.3 ozs. High Density Gel Foam
Woven Secondary	3.2 ozs. Actionbac
Composite Thickness125" (1/8" inch)
Density	22.2 pounds per cubic foot
Compression Set	25% maximum

Typical Properties	Delamination (ASTM D-3936)2.9 lbs. average*
	Tuftbind (ASTM D-1335)5.5 lbs. average*
	Radiant Panel (ASTM E-648)Class I*
	Smoke Density (ASTM E-662)Less than 350 DM Flaming*
	Moisture ResistancePasses British Spillage Test Method*

*As tested on Duration 32 Style. Results will vary with carpet construction.